
WELDSTER
Robustly Smart, Nothing Less.
FCAW
TIG
MMA
MIG - MAG
PAC
ROCKET MIX 160
1 YEAR WARRANTY
WELDSTER.com

WELDSTER

Robustly Smart, Nothing Less.

INDEX

03 BLAZER 160

04 BLAZER 200

05 ROCKET 140

06 ROCKET 160

07 ROCKET MIX 200

08 ROCKET MIX 220

09 BETA 250

10 GLIDER 45

11 BETA 353

12 BETA 383

13 ALPHA 100

14 DELTA

WELDSTER

Robustly Smart, Nothing Less.

BLAZER 160

220V | MMA / TIG LIFT ARC



High-contrast LED display for easy and quick reading.
Easy to use, with an excellent arc.

1 YEAR WARRANTY

TECHNICAL SPECIFICATIONS

CONNECTION	220V - 50/60Hz +/-10%
AMPERAGE RANGE	10-160A
DUTY CYCLE at 40°C	45%
OPEN CIRCUIT VOLTAGE U0	70V
MODES	MMA / TIG LIFT
CONNECTORS	QUICK CONNECTORS 1/2" (13mm)
IP	IP21S
DISPLAY TYPE	LED DISPLAY
ADJUSTMENT	KNOB
GENERATORS	Not recommended
EXTENSIONS (INPUT)	Up to 5m - AWG8
EXTENSIONS (OUTPUT)	Up to 5m - AWG2
Ø ELECTRODES	Ø1/16" to 1/8" (1.6mm to 3.2mm),
ELECTRODE TYPES	6013,7018, 6010, 6011
Included accessories	Ground clamp + Electrode holder set

DRB-160-220

WELDSTER

Robustly Smart, Nothing Less.



BLAZER 200

220V | MMA / TIG LIFT ARC

High-contrast LED display for easy and quick reading.
Easy to use, with an excellent arc.

1 YEAR WARRANTY

TECHNICAL SPECIFICATIONS

CONNECTION	220V - 50/60Hz +/-10%
AMPERAGE RANGE	10-200A
DUTY CYCLE at 40°C	45%
OPEN CIRCUIT VOLTAGE U0	70V
MODES	MMA / TIG LIFT
CONNECTORS	QUICK CONNECTORS 1/2" (13mm)
IP	IP21S
DISPLAY TYPE	LED DISPLAY
ADJUSTMENT	KNOB
GENERATORS	Not recommended
EXTENSIONS (INPUT)	Up to 5m - AWG8
EXTENSIONS (OUTPUT)	Up to 5m - AWG2
Ø ELECTRODES	Ø1/16" to 1/8" (1.6mm to 3.2mm), 6013,7018,
ELECTRODE TYPES	6010, 6011
INCLUDED ACCESSORIES	Ground clamp + Electrode holder set

DRB-200-220

WELDSTER

Robustly Smart, Nothing Less.

ROCKET MIX 140

Multi-process MMA/TIG/FCAW 140A unit, LED Display, and Synergic Control

High-contrast LED display
for easy and quick reading.
Connectable torch.
3 welding modes; FCAW, MMA
AND TIG LIFT
SYNERGIC MIG



*MODEL WITHOUT DISPLAY

1 YEAR WARRANTY

MULTI-PROCESS INVERTER UNIT
FOR WELDING, FLUXCORE (FCAW)
MMA and TIG (LIFT ARC)

TECHNICAL SPECIFICATIONS

CONNECTION	220V - 50/60Hz +/-10%
AMPERAGE RANGE	10-140A
DUTY CYCLE at 40°C	45%
OPEN CIRCUIT VOLTAGE U0	56V
MODES	FCAW / MMA / TIG LIFT
TIG TYPE	LIFT ARC
CONNECTORS	QUICK CONNECTORS 3/8" (9mm)
IP	IP21S
DISPLAY TYPE	LED DISPLAY
ADJUSTMENT	KNOB
GENERATORS	Not recommended
EXTENSIONS (INPUT)	Up to 5m - AWG8
EXTENSIONS (OUTPUT)	Up to 5m - AWG2
SPOOL	1KG (Ø100mm.)
WIRE TYPE	SELF-SHIELDED TUBULAR (FCAW), GASLESS

DMR-140-220

WELDSTER

Robustly Smart, Nothing Less.

ROCKET MIX 160

160/220V | MMA- FCAW - TIG



Large, high-contrast LED display for easy and quick reading.
Connectable torch for flux-cored wire, with 2T, 4T and spot welding function.
3 operating modes for self-shielded flux-cored wire: SYNERGIC, MANUAL, AND "AI"
HOT START, ARC FORCE FOR electrode.

MULTI

1 YEAR WARRANTY

TECHNICAL SPECIFICATIONS

CONNECTION	220V - 50/60Hz +/-10%
AMPERAGE RANGE	10-160A
DUTY CYCLE at 40°C	45%
OPEN CIRCUIT VOLTAGE U0	60V
MODES	FCAW / MMA / TIG LIFT
TIG TYPE	LIFT ARC
CONNECTORS	QUICK CONNECTORS 3/8" (9mm)
IP	IP21S
DISPLAY TYPE	LED DISPLAY SYNERGIC AI
ADJUSTMENT	KNOB
GENERATORS	Not recommended
EXTENSIONS (INPUT)	Up to 5m - AWG8
EXTENSIONS (OUTPUT)	Up to 5m - AWG2
SPOOL	1KG (Ø100mm.)
WIRE TYPE	SELF-SHIELDED TUBULAR (FCAW), GASLESS

DMR-160-220

WELDSTER

Robustly Smart, Nothing Less.

ROCKET MIX 200

200A / 220V |MMA/TIG/MIG-MAG/FCAW



High-contrast LED display for easy and quick reading.

Torch with EURO CONNECTOR for flux-cored wire.

4 functions in 1 unit

MMA
TIG LIFT
MIG-MAG
FCAW





TECHNICAL SPECIFICATIONS

CONNECTION	220V - 50/60Hz +/-10%
AMPERAGE RANGE	10-200A
DUTY CYCLE at 40°C	45%
OPEN CIRCUIT VOLTAGE U0	65V
MODES	MIG MAG / FCAW / MMA / TIG LIFT
TIG TYPE	LIFT ARC
CONNECTORS	QUICK CONNECTORS 3/8" (9mm)
IP	IP21S
DISPLAY TYPE	LED DISPLAY
ADJUSTMENT	KNOB
GENERATORS	Not recommended
EXTENSIONS (INPUT)	Up to 5m - AWG8
EXTENSIONS (OUTPUT)	Up to 5m - AWG2
SPOOL	5KG (Ø200mm.)
WIRE TYPE	SOLID, FLUX AND SELF-SHIELDED

DMR 200-200

WELDSTER

Robustly Smart, Nothing Less.

ROCKET MIX 220

220A/230V / MMA / TIG / MIG / MAG / FCAW



Large, high-contrast LCD display
for easy and quick reading.
Connectable torch for flux-cored wire,
with 2T, 4T and spot welding function.
3 operating modes for self-shielded
flux-cored wire:
SYNERGIC, MANUAL, AND "AI"
HOT START, ARC FORCE FOR electrode.
4-IN-1 UNIT
MMA, TIG LIFT, MIG-MAG , FCAW

MULTI

1 YEAR WARRANTY

TECHNICAL SPECIFICATIONS

CONNECTION	220V - 50/60Hz +/-10%
AMPERAGE RANGE	10-200A
DUTY CYCLE at 40°C	45%
OPEN CIRCUIT VOLTAGE U0	65V
MODES	MIG MAG / FCAW / MMA / TIG LIFT
TIG TYPE	LIFT ARC
CONNECTORS	QUICK CONNECTORS 3/8" (9mm)
IP	IP21S
DISPLAY TYPE	LED DISPLAY SYNERGIC AI
ADJUSTMENT	BUTTON + KNOBS
GENERATORS	Not recommended
EXTENSIONS (INPUT)	Up to 5m - AWG8
EXTENSIONS (OUTPUT)	Up to 5m - AWG2
SPOOL	5KG (Ø200mm.)
WIRE TYPE	SOLID, FLUX AND SELF-SHIELDED

DMR 220-220

WELDSTER

Robustly Smart, Nothing Less.

GLIDER 45

High-contrast LED display for easy and quick reading. Easy to use, with an excellent arc.



*MODEL WITHOUT DISPLAY

1 YEAR WARRANTY

TECHNICAL SPECIFICATIONS

CONNECTION	220V - 50/60Hz +/-10%
AMPERAGE RANGE	10-45A
DUTY CYCLE at 40°C	40%
OPEN CIRCUIT VOLTAGE U0	320V
MODES	PLASMA CUTTING
START	HF
CONNECTORS	QUICK CONNECTORS 3/8" (9mm)
IP	IP21S
DISPLAY TYPE	LED DISPLAY
ADJUSTMENT	BUTTON + KNOB
GENERATORS	Not recommended
EXTENSIONS (INPUT)	Up to 5m - AWG8
EXTENSIONS (OUTPUT)	Up to 5m - AWG2
Cutting capacity	14 mm separation recommended for 10mm.
Included accessories	Ground clamp + 4m plasma torch set.

DPG-045-220

WELDSTER

Robustly Smart, Nothing Less.

BETA 250

Robust helmet, 35x95 mm visor, interchangeable battery, shade DIN 3/11.



VIEWING AREA 3.9"
Dual Digital Sensor
Hybrid Solar And Battery Power Supply (Interchangeable).
Ultra Fast Processor Ultra-Sensitivity In Low Light.

Robust welding helmet with a wide viewing area of 35x95 mm and interchangeable battery, ensuring maximum efficiency. Equipped with fixed shade DIN 3/11, it offers constant protection against radiation and sparks. Designed for durability and comfort, it is ideal for professionals seeking precision and safety in every weld.

TECHNICAL SPECIFICATIONS

Viewing Area	35 X 95 mm / 3.9 "
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR
Response Time	1/25000s.
Modes	MMA / TIG / MIG
Minimum Amperage	15AMP
Sensitivity Regulation	INTERNAL
Shade Regulation	GRIND 3/11
Type of Vision	COLOR HD
Material	ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSB-383-GLD

WELDSTER

Robustly Smart, Nothing Less.

BETA 353

WELDING HELMET WITH DIN 3/11 AND COLOR VISION
Robust helmet, 35x90mm visor, interchangeable battery, shade DIN 3/11.



VIEWING AREA 3.8"
Dual Digital Sensor
Hybrid Solar And Battery Power Supply (Interchangeable).
Ultra Fast Processor Ultra-Sensitivity In Low Light.

Robust welding helmet with a wide viewing area of 35x90 mm and interchangeable battery, ensuring maximum efficiency. Equipped with fixed shade DIN 3/11, it offers constant protection against radiation and sparks. Designed for durability and comfort, it is ideal for professionals seeking precision and safety in every weld.

TECHNICAL SPECIFICATIONS

Viewing Area	35x90mm / 3.8"
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR + REPLACEABLE BATTERY (2032)
Response Time	1/25000s.
Modes	MMA / TIG / MIG
Min. Amperage	25AMPS
Delay Time	FIX
Sensitivity Regulation	FIX
Shade Regulation	FIX, DIN 3 / 11
Type of Vision	COLOR HD
Material	ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSB-353

WELDSTER

Robustly Smart, Nothing Less.





BETA 383
MADMETAL GOLD

Auto-darkening welding helmet
Precision protection. Nothing less.

The **BETA 383 MADMETAL** helmet by Weldster combines a radical design with advanced technology for the modern welder. Equipped with a wide viewing area of 93 × 43 mm, 2 high-speed digital sensors, and a replaceable CR2032 battery, it ensures active and reliable protection at all times. Its 4-point harness with integral padding provides maximum comfort, while the external shade regulation **DIN 9-13** allows quick and precise adjustment. Additionally, the filter with technology GOLDARIZED offers enhanced protection against UV and IR radiation, providing a clearer, more stable visual experience and free from eye fatigue.

Filter with technology GOLDARIZED for **UV/IR** protection. Advanced optical filtering that blocks ultraviolet and infrared radiation from the welding arc. Improves visual comfort and significantly reduces eye fatigue.

Excellent performance in **MMA, FLUX CORED, MIG, MAG and TIG** processes. Provides continuous protection against radiation and sparks. Equipped with a gold filter that provides relaxing visual comfort.

- UV/IR GOLDARIZED Filter
- Matte metallic paint design **MADMETAL**
- High-Speed Sensors
- Customizable sensitivity and delay adjustment
- color vision
- External Shade **DIN 9-13**
- Mode **GRINDING DIN 4**
- Power Supply **CR2032**
- Structure Robust & Light
- **ErgoLock 4X™ System** Comfort Points

TECHNICAL SPECIFICATIONS

Viewing Area	43x93mm / 4.0”
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR + REPLACEABLE BATTERY (2032)
Response Time	1/25000s.
Modes	MMA / TIG / MIG
Minimum Amperage	15AMP
Sensitivity Regulation	INTERNAL
Shade Regulation	GRIND 4, ADJUSTABLE DIN 9-13
Vision Type	COLOR HD GOLDARIZED
Material	ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSB-383-SIL

WELDSTER

Robustly Smart, Nothing Less.



BETA 383

MADMETAL GREEN

Auto-darkening welding helmet
Precision protection. Nothing less.

The **BETA 383 MADMETAL** helmet by Weldster combines a radical design with advanced technology for the modern welder. Equipped with a wide viewing area of 93 × 43 mm, 2 high-speed digital sensors, and a replaceable CR2032 battery,

it ensures active and reliable protection at all times. Its 4-point harness with integral padding provides maximum comfort, while the external shade regulation **DIN 9-13**

allows quick and precise adjustment.

Additionally, the filter with technology GOLDARIZED offers enhanced protection against UV and IR radiation, providing a clearer, more stable visual experience and free from eye fatigue.

Filter with technology GOLDARIZED for **UV/IR** protection. Advanced optical filtering that blocks ultraviolet and infrared radiation from the welding arc. Improves visual comfort and significantly reduces eye fatigue.

Excellent performance in **MMA, FLUX CORED, MIG, MAG and TIG** processes. Provides continuous protection against radiation and sparks. Equipped with a gold filter that provides relaxing visual comfort.

- UV/IR GOLDARIZED Filter
- Matte metallic paint design **MADMETAL**
- High-Speed Sensors
- Customizable sensitivity and delay adjustment
- color vision
- External Shade **DIN 9-13**
- Mode **GRINDING DIN 4**
- Power Supply **CR2032**
- Structure Robust & Light
- **ErgoLock 4X™ System** Comfort Points

TECHNICAL SPECIFICATIONS

Viewing Area	43x93mm / 4.0”
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR + REPLACEABLE BATTERY (2032)
Response Time	1/25000s.
Modes	MMA / TIG / MIG
Minimum Amperage	15AMP
Sensitivity Regulation	INTERNAL
Shade Regulation	GRIND 4, ADJUSTABLE DIN 9-13
Vision Type	COLOR HD GOLDARIZED
Material	ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSB-383-GRN

WELDSTER

Robustly Smart, Nothing Less.



BETA 383
MADMETAL SILVER

Auto-darkening welding helmet
Precision protection. Nothing less.

The **BETA 383 MADMETAL** helmet by Weldster combines a radical design with advanced technology for the modern welder. Equipped with a wide viewing area of 93 × 43 mm, 2 high-speed digital sensors, and a replaceable CR2032 battery, it ensures active and reliable protection at all times. Its 4-point harness with integral padding provides maximum comfort, while the external shade regulation **DIN 9-13** allows quick and precise adjustment.

Additionally, the filter with technology GOLDARIZED offers enhanced protection against UV and IR radiation, providing a clearer, more stable visual experience and free from eye fatigue.

Filter with technology GOLDARIZED for **UV/IR** protection. Advanced optical filtering that blocks ultraviolet and infrared radiation from the welding arc. Improves visual comfort and significantly reduces eye fatigue.

Excellent performance in **MMA, FLUX CORED, MIG, MAG and TIG** processes. Provides continuous protection against radiation and sparks. Equipped with a gold filter that provides relaxing visual comfort.

- UV/IR GOLDARIZED Filter
- Matte metallic paint design **MADMETAL**
- High-Speed Sensors
- Customizable sensitivity and delay adjustment
- color vision
- External Shade **DIN 9-13**
- Mode **GRINDING DIN 4**
- Power Supply **CR2032**
- Structure Robust & Light
- **ErgoLock 4X™ System** Comfort Points

TECHNICAL SPECIFICATIONS

Viewing Area	43x93mm / 4.0"
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR + REPLACEABLE BATTERY (2032)
Response Time	1/25000s.
Modes	MMA / TIG / MIG
Minimum Amperage	15AMP
Sensitivity Regulation	INTERNAL
Shade Regulation	GRIND 4, ADJUSTABLE DIN 9-13
Vision Type	COLOR HD GOLDARIZED
Material	ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSB-383-SIL

WELDSTER

Robustly Smart, Nothing Less.

ALPHA 100



FIXED SHADE WELDING MASK DIN11

Robust helmet, visor 100x40mm

Viewing area of 4.3"

FLIP-UP / ABATIBLE

Welding mask with DIN 11 inactinic filter for protection against radiation and particle projections caused during welding work: MIG, MAG, TIG or arc welding.

Includes DIN11 opacity inactinic filter with optical quality and distortion-free vision for continuous welding processes preventing eye fatigue.

Welding mask equipped with harness and strap for head adjustment, flip-up lenses

TECHNICAL SPECIFICATIONS

Viewing Area	100X40mm / 4.3"
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR + REPLACEABLE BATTERY (2032)
Response Time Modes	1/25000s.
Minimum Amperage	MMA / TIG / MIG
Sensitivity Regulation	0AMPS
Vision Type	Passive / Fixed, SHADE 11
Material	Green infrared lenses, compliant EN169 ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSB-353

WELDSTER

Robustly Smart, Nothing Less.



DELTA 353

MADMETAL BLACK

Auto-darkening welding helmet
Precision protection. Nothing less.

The **DELTA 383 BLACK** helmet by Weldster combines a radical design with advanced technology for the modern welder. Equipped with a wide viewing area of 90x35, 2 high-speed digital sensors, and a replaceable CR2032 battery, it ensures active and reliable protection at all times.

Its 3-point harness with integral padding provides maximum comfort. Fixed Regulation **DIN 4-11** allows quick and precise adjustment.

Additionally, the filter with technology REAL COLOR offers enhanced protection against UV and IR radiation, providing a clearer, more stable visual experience free from eye fatigue.

Filter with technology REAL COLOR for **UV/IR** protection. Advanced optical filtering that blocks ultraviolet and infrared radiation from the welding arc. Improves visual comfort and significantly reduces eye fatigue.

Excellent performance in **MMA, FLUX CORED, MIG, MAG and TIG** processes. Provides continuous protection against radiation and sparks. Equipped with a gold filter that provides relaxing visual comfort.

- Comfortable design
- High-Speed Sensors
- REAL COLOR
- External Shade **DIN 9-13**
- Mode **GRINDING DIN 4**
- Power Supply **CR2032**
- Structure Robust & Light
- **ErgoLock 3X™ System** Comfort Points

TECHNICAL SPECIFICATIONS

Viewing Area	90x35mm
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR + REPLACEABLE BATTERY (2032)
Switching Time	1/25000s.
Modes	MMA / TIG / MIG
Minimum Amperage	25AMPS
Shade Regulation	DIN 3 / 11
Vision Type	COLOR HD REAL COLOR
Material	ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSD-353

WELDSTER

Robustly Smart, Nothing Less.





DELTA 383

MADMETAL YELLOW

Auto-darkening welding helmet
Precision protection. Nothing less.

The **DELTA 383 YELLOW** helmet by Weldster combines a radical design with advanced technology for the modern welder. Equipped with a wide viewing area of 93x43 mm, 2 high-speed digital sensors, and a replaceable CR2032 battery, it ensures active and reliable protection at all times.
Its 3-point harness with integral padding provides maximum comfort, while the external shade regulation **DIN4 / 9-13** allows quick and precise adjustment.
Additionally, the filter with technology REAL COLOR offers enhanced protection against UV and IR radiation, providing a clearer, more stable visual experience free from eye fatigue.

Filter with technology REAL COLOR for **UV/IR** protection. Advanced optical filtering that blocks ultraviolet and infrared radiation from the welding arc. Improves visual comfort and significantly reduces eye fatigue.

Excellent performance in **MMA, FLUX CORED, MIG, MAG and TIG** processes. Provides continuous protection against radiation and sparks. Equipped with a gold filter that provides relaxing visual comfort.

- Comfortable design
- High-Speed Sensors
- REAL COLOR
- External Shade **DIN 9-13**
- Mode **GRINDING DIN 4**
- Power Supply **CR2032**
- Structure Robust & Light
- **ErgoLock 3X™ System** Comfort Points

TECHNICAL SPECIFICATIONS

Viewing Area	93x43 mm
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR + REPLACEABLE BATTERY (2032)
Response Time	1/25000s.
Modes	MMA / TIG / MIG
Minimum Amperage	15AMP
Shade Regulation	GRIND 4, ADJUSTABLE DIN 9-13
Vision Type	COLOR HD REAL COLOR
Material	ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSD-383-YEL

WELDSTER

Robustly Smart, Nothing Less.



DELTA 383

MADMETAL SILVER

Auto-darkening welding helmet
Precision protection. Nothing less.

The **DELTA 383 MADMETAL** helmet by Weldster combines a radical design with advanced technology for the modern welder. Equipped with a wide viewing area of 93x43 mm, 2 high-speed digital sensors, and a replaceable CR2032 battery, it ensures active and reliable protection at all times. Its 3-point harness with integral padding provides maximum comfort, while the external shade regulation **DIN 9-13** allows quick and precise adjustment.

Additionally, the filter with technology REAL COLOR offers enhanced protection against UV and IR radiation, providing a clearer, more stable visual experience free from eye fatigue.

Filter with technology REAL COLOR for **UV/IR** protection. Advanced optical filtering that blocks ultraviolet and infrared radiation from the welding arc. Improves visual comfort and significantly reduces eye fatigue.

Excellent performance in **MMA, FLUX CORED, MIG, MAG and TIG** processes. Provides continuous protection against radiation and sparks. Equipped with a gold filter that provides relaxing visual comfort.

- Comfortable design
- High-Speed Sensors
- REAL COLOR
- External Shade **DIN 9-13**
- Mode **GRINDING DIN 4**
- Power Supply **CR2032**
- Structure Robust & Light
- **ErgoLock 3X™ System** Comfort Points

TECHNICAL SPECIFICATIONS

Viewing Area	93x43 mm
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR + REPLACEABLE BATTERY (2032)
Response Time	1/25000s.
Modes	MMA / TIG / MIG
Minimum Amperage	15AMP
Shade Regulation	GRIND 4, ADJUSTABLE DIN 9-13
Vision Type	COLOR HD REAL COLOR
Material	ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSD-383-SIL

WELDSTER

Robustly Smart, Nothing Less.





DELTA 383

MADMETAL GOLD

Auto-darkening welding helmet
Precision protection. Nothing less.

The **DELTA 383 MADMETAL** helmet by Weldster combines a radical design with advanced technology for the modern welder. Equipped with a wide viewing area of 93x43 mm, 2 high-speed digital sensors, and a replaceable CR2032 battery, it ensures active and reliable protection at all times.

Its 3-point harness with integral padding provides maximum comfort, while the external shade regulation **DIN 9-13** allows quick and precise adjustment.

Additionally, the filter with technology REAL COLOR offers enhanced protection against UV and IR radiation, providing a clearer, more stable visual experience and free from eye fatigue.

Filter with technology REAL COLOR for **UV/IR** protection. Advanced optical filtering that blocks ultraviolet and infrared radiation from the welding arc. Improves visual comfort and significantly reduces eye fatigue.

Excellent performance in **MMA, FLUX CORED, MIG, MAG and TIG** processes. Provides continuous protection against radiation and sparks. Equipped with a gold filter that provides relaxing visual comfort.

Comfortable design

High-Speed Sensors

REAL COLOR

External Shade **DIN 9-13**

Mode **GRINDING DIN 4**

Power Supply **CR2032**

Structure Robust & Light

ErgoLock 3X™ System Comfort Points

TECHNICAL SPECIFICATIONS

Viewing Area	93x43 mm
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR + REPLACEABLE BATTERY (2032)
Response Time	1/25000s.
Modes	MMA / TIG / MIG
Minimum Amperage	15AMP
Sensitivity Regulation	INTERNAL
Shade Regulation	GRIND 4, ADJUSTABLE DIN 9-13
Vision Type	COLOR HD REAL COLOR
Material	ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSD-383-GLD

WELDSTER

Robustly Smart, Nothing Less.





DELTA 383

MADMETAL GREEN

Auto-darkening welding helmet
Precision protection. Nothing less.

The **DELTA 383 MADMETAL** helmet by Weldster combines a radical design with advanced technology for the modern welder. Equipped with a wide viewing area of 93x43 mm, 2 high-speed digital sensors, and a replaceable CR2032 battery,

it ensures active and reliable protection at all times. Its 3-point harness with integral padding provides maximum comfort, while the external shade regulation **DIN 9-13**

allows quick and precise adjustment. Additionally, the filter with technology REAL COLOR offers enhanced protection against UV and IR radiation, providing a clearer, more stable visual experience and

free from eye fatigue.

Filter with technology REAL COLOR for **UV/IR** protection. Advanced optical filtering that blocks ultraviolet and infrared radiation from the welding arc. Improves visual comfort and significantly reduces

eye fatigue.

Excellent performance in **MMA, FLUX CORED, MIG, MAG and TIG** processes. Provides continuous protection against radiation and sparks. Equipped with a gold filter that provides relaxing visual comfort.

Comfortable design

High-Speed Sensors

REAL COLOR

External Shade **DIN 9-13**

Mode **GRINDING DIN 4**

Power Supply **CR2032**

Structure Robust & Light

ErgoLock 3X™ System Comfort Points

TECHNICAL SPECIFICATIONS

Viewing Area	93x43 mm
Weight	0.4 Kg
Power Supply	HYBRID, SOLAR + REPLACEABLE BATTERY (2032)
Response Time	1/25000s.
Modes	MMA / TIG / MIG
Minimum Amperage	15AMP
Shade Regulation	GRIND 4, ADJUSTABLE DIN 9-13
Vision Type	COLOR HD REAL COLOR
Material	ROBUST PP
Certifications	ANSI / CSA Z87.1 2010

DSD-383-GRN

WELDSTER

Robustly Smart, Nothing Less.



WELDING **CONSUMABLES**
WELDING AND FILLER METALS
2025

weldster.com

RODSTER 6010
DWF-610

Classifications

EN ISO 2560-A	EN ISO 2560-B	AWS A5.1	AWS A5.1M
E 38 0 C 2 2	E 43 11 A	E 6010	E 4310

Features and application types

Electrode with special cellulosic-sodium coating with iron powder. It has excellent arc transfer, very good penetration and arc stability. An excellent electric arc with easy operation allows working in all positions. It can be used with drag technique and provides very good radiographic quality.

Base materials

Designed for joint welding of oil pipelines, gas pipelines, shipbuilding, carbon steel structures and pressure vessels.

Weld analysis

C 0.11	SI 0.36	MN 0.63	P 0.015
S 0.013	Ni 0,02	Cr 0.03	V 0.01

Mechanical properties

Tensile strength	Yield strength	Elongation	Charpy V-notch impact resistance at -29 °C
43.5-50.5 Kg /mm2	36.5 43.5 Kg/mm2	22-33%	27-100 Joules.

NOTE: Tests performed under AWS A5.1

Operating data

POSITIONS	POLARITY	PACKAGING	IDENTIFICATION	ØMM.	Ø MM.	L MM.	AMPS (A)
	DC+ / DC - Negative or Positive polarity	20 KG	DRF-610-M25 DRF-610-M32 DRF-610-M40 DRF-610-M50	2.5 3.2 4.0 4.8	3/32 1/8 5/32 3/16	300 350 350 450	50-90 70-120 90-155 120-180

REV. 2025-2

RODSTER 6011
DWF-611

Classifications

EN ISO 2560-A	EN ISO 2560-B	AWS A5.1	AWS A5.1M
E 38 2 C 12	E 43 11	E 6011	E 4311

Features and application types

Electrode with special coating that characterizes its smooth operation, forming very good penetration due to its special cellulosic coating. It generates low material loss from spatter. Its radiographic quality is superior to grade 2 of the AWS A 5.1 specification. Works with alternating current and direct current electrode positive. Maintain a medium-length arc.

Base materials

Used for welding all types of low carbon steel, pipe joints, shipbuilding, carbon steel structures and pressure vessels. Ideal for work on ZINC-coated sheets.

Weld analysis


C 0.08	SI 0.31	MN 0.58	P 0.017
S 0.018	Ni 0,02	Cr 0.03	V 0.01

Mechanical properties

Tensile strength	Yield strength	Elongation	Charpy V-notch impact resistance at -29 °C
44.3-52.5 Kg /mm2	36.5 43.5 Kg/mm2	22-35%	27-100 Joules.

NOTE: Tests performed under AWS A5.1

Operating data

POSITIONS	POLARITY	PACKAGING	IDENTIFICATION	Ø MM.	Ø MM.	L MM.	AMPS (A)
	AC or DC+ / DC - Negative or Positive polarity	20 KG	DRF-611-M25 DRF-611-M32 DRF-611-M40	2.5 3.2 4.0	3/32 1/8 5/32	300 350 350	50-80 70-115 90-160

REV. 2025-2

RODSTER ECO-PLUS
DWF-613

Classifications

EN ISO 2560-A	EN ISO 2560-B	AWS A5.1	AWS A5.1
E 38 0 R 11	E 43 13A	E 6013	E 43 13A

Features and application types

Electrode with special European coating, easy to handle, developed for welds requiring medium penetration.
The deposited metal produces a uniform, smooth layer, without notches or undercuts, leaving beads with excellent appearance and easy slag removal. Works with alternating current or direct current with negative (-) or positive (+) polarity. Generates less smoke.

Base materials

Designed for general iron construction, metal fabrication with thin sheet, manufacturing of doors, windows, grilles, ducts, body assembly and general ornamentation.

Weld analysis


C 0.06	SI 0.35	MN 0.40	P 0.020
S 0.011	Ni 0.02	Cr 0.03	V 0.01

Mechanical properties

Tensile strength	Yield strength	Elongation	Charpy V-notch impact resistance at -29 °C
42-52. Kg /mm2	34- 44 Kg/mm2	22-28%	40-110 Joules..

NOTE: Tests performed under AWS A5.1

Operating data

POSITIONS	POLARITY	PACKAGING	IDENTIFICATION	ØMM.	Ø MM.	L MM.	AMPS (A)
	AC or DC+ / DC - Negative or Positive polarity	20 KG	DRF-611-M25 DRF-611-M32 DRF-611-M40	2.5 3.2 4.0	3/32 1/8 5/32	300 350 350	50-90 70-120 90-155

REV. 2025-2

RODSTER BASIC-18
DWF-718

Classifications

EN ISO 2560-A	EN ISO 2560-B	AWS A5.1	AWS A5.1
E 42 3 B 32 H10	E 49 18 A U H10	E 7018	E 4918

Features and application types

Electrode with special basic low-hydrogen coating, designed for use with direct current, positive polarity (+). It presents excellent transfer and stability. An excellent electric arc with easy operation allows working in all positions. A short arc is recommended, avoiding abrupt movements. It presents a high deposition rate and low spatter losses.

Base materials

Designed for joint welding of oil pipelines, gas pipelines, shipbuilding, carbon steel structures and pressure vessels, ideal for structures, boilers, railroad cars, etc.

Weld analysis


C 0.07	SI 0.61	MN 0.87	P 0.015
S 0.011	Ni 0.02	Cr 0.03	V 0.01

Mechanical properties

Tensile strength	Yield strength	Elongation	Charpy V-notch impact resistance at -29 °C
51-59 Kg /mm2	43.5- 51 Kg/mm2	23-36 %	29-70 Joules.

NOTE: Tests performed under AWS A5.1

Operating data

POSITIONS	POLARITY	PACKAGING	IDENTIFICATION	Ø MM.	Ø MM.	L MM.	AMPS (A)
	DC+ / DC - Negative or Positive polarity	20 KG	DRF-718-M25 DRF-718-M32 DRF-718-M40 DRF-718-M50	2.5 3.2 4.0 4.8	3/32 1/8 5/32 3/16	300 350 350 350	70-100 100-145 135-200 170-270

REV. 2025-2

MIGSTER C-S6

DWF-CS6

Classifications

EN ISO 14341 A	EN ISO 14341 B	AWS A5.18	KS D7025
G 42 2 C G3Si 1	Y GW12	E ER70S6	G49A 3C G6

Features and application types

Solid wire with high levels of Silicon and Manganese that provide excellent deoxidation characteristics, especially when welding oxidized sheets. It presents a very fluid arc and therefore a flatter weld bead. Works with CO2 or argon CO2 or oxygen mix, can work in all positions when configured for short circuit transfer.

Base materials

Designed for joint welding of thin sheets, used in shaft repair, tank manufacturing, car bodies, agricultural implements, automobile rims, vessels, structures, etc.

Weld analysis


C 0.07	SI 0.86	MN 1.53	P 0.012
S 0.007	Ni 0.50		

Mechanical properties

Tensile strength	Yield strength	Elongation	Charpy V-notch impact resistance at -29 °C
50-60.5 Kg /mm2	42 52.5 Kg/mm2	22-30%	27-120 Joules.

NOTE: Tests performed under AWS A5.1

Operating data

POSITIONS	POLARITY	PACKAGING	IDENTIFICATION	Ø MM.	Ø MM.	L MM.	AMPS (A)
	CV Constant Voltage Positive Polarity	1 kg ,5Kg,15kg 1Kg,5 Kg, 15Kg 5Kg, 15 Kg 15 Kg	DWF-CS6-X08 DWF-CS6-X09 DWF-CS6-X12 DWF-CS6-X16 X = 1 (1KG) 5 (KG) B (15KG)	0.8 0.9 1.2 1.6	0,030 0.035 0.045 0.062	1-5-15 1-5-15 5-15 15	60-160 80-220 100-340 250-500

REV. 2025-2

FLUXSTER

DWF-FLX

Classifications

EN ISO 17632-A	EN ISO 17632-B	AWS A5.20-13	KS D 7104
T 42 Z V N 1	T 49 Z TG -1NS	E 71T-GS	JIS Z 3313

Features and application types

Self-shielded flux-cored wire designed to work in all positions. Excellent for single or multiple pass use, provides a smooth and very stable arc with easy slag removal and low spatter.

Base materials

Designed for joint welding of carbon steel sheets and galvanized sheets, ideal for field work in ornamentation and metalworking, ideal for welding structures, machinery parts repair, car bodies, tanks, pressure pipes and tanks.

Weld analysis


C 0.10	SI 0.10	MN 0.55	P 0.014
S 0.006	Ni 1.21		

Mechanical properties

Tensile strength	Yield strength	Elongation	Charpy V-notch impact resistance at -29 °C
70 Kg /mm2	44 Kg/mm2	22 %	27-100 Joules.

NOTE: Tests performed under AWS A5.1

Operating data

POSITIONS	POLARITY	PACKAGING	IDENTIFICATION	Ø MM.	Ø MM.	L MM.	AMPS (A)
	CV - CC	1Kg	DWF-FLX-108	0.8	0,030	16-18	80-120
	DC+ / DC -	1Kg	DWF-FLX-109	0.9	0.035	18-24	80-180
	Negative	5Kg	DWF-FLX-512	0.8	0.045	16-18	80-120
	polarity	5Kg	DWF-FLX-509	0,9	0.062	18-24	80-180

X = 1 (1KG) 5 (KG) B (15KG)

REV. 2025-2

PRODUCT
CATALOG

Weldster offers you a complete line of precision multi-process welding equipment of high quality to meet the needs of your specific application.

1 YEAR WARRANTY

WELDSTER

Robustly Smart, Nothing Less.



weldster.com